



Product Overview

Velura Salt Free Conditioner Treatment System

Designed for 1-6 bathroom homes on city or municipal water supply

The Filtrion Velura Series is our whole home salt-free water conditioning treatment system. It is designed for use on city or municipal water and can support homes with up to 6 full bathrooms based on the system configuration. It is effective in reducing and prevented scale accumulation and prolongs the life of plumbing, fixtures and appliances. It is also an excellent addition to ensure warranties on tankless water heaters are not voided due to scale accumulation.

The system utilizes a high ppressure FRP (fiberglass reinforced polymer) tank with 1" NPT ports. The salt-free vessel contains our proprietary scale prevention media that is effective in water hardness up to 70 GPG (grains per gallon) or 1,197 ppm making it ideal for high water hardness applications.


This unit is designed to be installed at the water main entry point and will provide a flow rate of up between 10-20 gallons per minute of flow. The standard inlet and outlet connections are 1" NPT and has a design pressure of 150 PSI (10 bar) with a maximum operating temperature of 120°F (45°C).

Features

- 1 Stage system designed for residential applications
- 1" NPT inlets & outlets
- No electricity, backwash or drain required
- Reduces and prevents the accumulation of scale
- Prolongs the life of plumbing, fixtures and appliances
- Keeps healthy minerals in your water.
- Conditions water without the slippery feel
- Effective in water hardness up to 70 GPG (1,197 PPM)
- High flow rate from 10-20 GPM
- Proven salt-free technology

Specifications

- Operating Temp: 40°F-120°F
- Max Pressure: 150 PSI
- Minimum Burst: 600 PSI
- Max Hardness: 70 GPG
- Flow Rate: 10-20 GPM



Product Specifications

Model No	Description	Flow Rate	Bathrooms	Household Size	Dimensions
FI-VE-100	Velura 10 GPM Salt-Free System	10 GPM,	1-3	1-3 people	8" x 44"
EI-VE-150	Velura 15 GPM Salt-Free System	15 GPM	4-5	4-5 people	10" x 54"
FI-VE-200	Velura 20 GPM Salt-Free System	20 GPM	6+	6+ people	12" x 52"

Applications

Residential Homes	Commercial Installations
Food Service	Brewing Applications
Hospitality Applications	Car Wash Facilities

Velura FI-VE-100



- 1-3 Bathroom Homes
- Salt-Free Conditioning
- 10 GPM Flow Rate
- Max Hardness: 70 GPG

Velura FI-VE-150



- 4-5 Bathroom Homes
- Salt-Free Conditionioing
- 15 GPM Flow Rate
- Max Hardness: 70 GPG

Velura FI-VE-200



- 6+ Bathroom Homes
- Salt-Free Conditioning
- 20 GPM Flow Rate
- Max Hardness: 70 GPG